



4P 40A Centre Off Changeover , Top

SFT440

Technical Properties

| | |
|---|-------------------------|
| Number of modules | 4 |
| Number of poles | 4 P |
| Rated operational voltage Ue | 400 V |
| Rated current | 40 A |
| Rated operational current in AC21 category A | 40 A |
| Rated operational current in AC21 category B | 40 A |
| Rated short-time withstand current I _s | 0,6 kA |
| Power loss per pole at I _n | 2,1 W |
| Total power loss under I _N | 8,4 W |
| Frequency | 50/60 Hz |
| Rated insulation voltage | 440 V |
| Rated impulse withstand voltage | 4000 V |
| Operating temperature | -20 to 50 °C |
| Electrical durability at nominal load in AC21 in operating cycles | 25000 |
| Acceptable current rating with AC22 category A | 40 A |
| Acceptable current rating with AC22 category B | 40 A |
| Number of mechanical operations | 200000 |
| Connection cross-sect. rigid cable | 1,5 / 16mm ² |
| Connection cross-sect. flexible cable | 1,5 / 10mm ² |
| Height of installed product | 83 mm |
| Width of installed product | 70 mm |
| Depth of installed product | 71 mm |
| Tightening torque | 1,8Nm |
| Protection index IP | IP20 |
| Standard text | IEC 60947-3 |