

# PRODUCT DATASHEET

## ST8S-EM 16 W/4000 1200 mm

LED STAR+ MOTION SENSOR T8 | LED tube with integrated motion sensor



---

### AREAS OF APPLICATION

- Corridors, stairways, parking garages
- Warehouses

---

### PRODUCT BENEFITS

- Integrated motion sensor with motion dependend dimming function
- Short payback period thanks to low energy consumption and maintenance costs
- Energy savings of up to 70 % compared to conventional T8 fluorescent lamp
- No bending thanks to glass technology
- Two year guarantee
- Instant flickerfree starting

---

### PRODUCT FEATURES

- LED alternative to classic T8 fluorescent lamps in CCG luminaires
- Luminous efficacy: up to 100 lm/W
- Two step dimming: 30 % and 100 % light output
- Lifetime: up to 30,000 h
- High color consistency:  $\leq 6$  SDCM
- Color rendering index  $R_a$ :  $\geq 80$



- Bright, robust and durable
- Uniform illumination

## TECHNICAL DATA

### Electrical data

Nominal wattage	16.00 W
Rated wattage	16.00 W
Nominal voltage	220...240 V
Nominal current	0.075 A
Power factor $\lambda$	0.90


### Photometrical data

Light color (designation)	Cool White
Rated color temperature	4000 K
Nominal luminous flux	1600 lm
Rated luminous flux	1600 lm
Color rendering index Ra	80
Lumen main.fact.at end of nom.life time	0.70
Color temperature	4000 K
Luminous flux	1600 lm
Color rendering index Ra	80
Standard deviation of color matching	$\leq 6$ sdc <sub>m</sub>

### Light technical data

Starting time	< 1.0 s
Warm-up time (60 %)	< 1.00 s
Rated beam angle (half peak value)	200.00 °

### Dimensions & weight



Product weight	220.00 g
----------------	----------

<b>Overall length</b>	1212 mm
-----------------------	---------

#### Temperatures & operating conditions

<b>Ambient temperature range</b>	-10...45 °C
----------------------------------	-------------

#### Lifespan

<b>Nominal lamp life time</b>	30000 h
<b>Rated lamp life time</b>	30000 h
<b>Number of switching cycles</b>	50000

#### Additional product data

<b>Base (standard designation)</b>	G13
<b>Mercury-free</b>	Yes

#### Capabilities

<b>Dimmable</b>	Yes
-----------------	-----

#### Certificates & standards

<b>Energy efficiency class</b>	A+
<b>Energy efficiency class</b>	A+
<b>Energy consumption</b>	18 kWh/1000h

#### Country-specific categorizations

<b>Order reference</b>	ST8S-1.2M 16W/8
------------------------	-----------------

#### Logistical data

<b>Temperature range at storage</b>	-20...80 °C
-------------------------------------	-------------

## EQUIPMENT / ACCESSORIES

- Suitable for operation on conventional control gear

## SAFETY ADVICE

Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.

## LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075067035	ST8S-EM 16 W/4000 1200 mm	Shipping carton box 25	1360 mm x 225 mm x 235 mm	71.91 dm <sup>3</sup>	8316.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**LEGAL ADVICE**

When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.