



CLEVERTRONICS ECONOMY LITHIUM WEATHERPROOF EXIT



PRODUCT INFORMATION

Catalogue Number	EWELED-LI
Description	Economy Lithium Weatherproof Emergency EXIT
Construction	Polycarbonate Clear Cover, Glass reinforced nylon PA66 base
Mounting	Wall, Ceiling single-sided & Ceiling double-sided
Dimensions L x W x H	410mm x 100mm x 272mm
Weight	2.8kg
Operating Mode	Maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 600mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	4 x LED, Surface Mounted onto a replaceable lamp bar - 50,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	1.1 Watts (Standby), 2.0 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =E2 C ₉₀ =E1.6
Impact Rating	IK10
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550195	BATT: LiFePO4 3.2V 600mAh 210mm lead, noBRKT
8002900	PCA:LED Strip ECFLED-LI CT10242-D1
8002880	PCA:Driver ECOLITH Cleverfit CT10240-L4

