



Gas soldering iron 30 to 125 W



Benefits

- Gas canister (38 ml for a use during 3 hours and a half average).
- Blow torch function for heatshrink tubes; simply undo the metal ring.



GENERAL INFORMATION

Technical details

Equivalent power: 30-125 W.
Bit temperature: 250-550 °C.

Instructions

1. Heating time: 15 seconds.

ACCESSORIES



Spare tip with 1.6 mm point



Deflector nozzle for heatshrink sleeving



Spare jet





Heat blower for gas soldering iron

 LOGISTIC INFORMATION

 Packaging



Blister package



Height (cm) : 3.4
 Length (cm) : 30.6
 Depth (cm) : 10.3
 Net weight (kg) : 0.15
 Gross weight (kg) : 0.2



 Outer package 1



Carton box

Height (cm) : 31.51
 Length (cm) : 21.82
 Depth (cm) : 20
 Net weight (kg) : 1.8
 Gross weight (kg) : 2.88





x 12.00

 Outer package 2



Carton box

Height (cm) : 35.2
 Length (cm) : 46.1
 Depth (cm) : 42.6
 Net weight (kg) : 7.2
 Gross weight (kg) : 12.6





x 48.00

 Outer package 3



Pallet

Height (cm) : 100
 Length (cm) : 120
 Depth (cm) : 82
 Net weight (kg) : 72
 Gross weight (kg) : 148.3



x 480.00