

Stainless steel barb lock PA 6.6 cable tie 295 x 4.8 mm UV black (x 100)



Characteristics

- Colour : **Black**
- Length (mm) : **295**
- Width (mm) : **4.8**
- Thickness (mm) : **1.5**
- Maximum clamping Ø (mm) : **81**
- Traction strength (N) : **220**
- Quantity per box : **100**

Benefits

- No resistance on tightening.
- High level of abrasion resistance.
- Halogen-free.
- UV-resistant.

Compliance marks



GENERAL INFORMATION

Technical details

- Pull-tie material: polyamide 6.6.
- Raw material flammability: UL94V-2.
- Barb material: stainless steel 304.
- Installation temperature: - 40 to +60 °C.
- Operating temperature: -40 to +85 °C.

Application(s)

These cable ties are designed for interior and exterior fixing applications. Perfect for environments where vibration is present, the metal barb ensures regular high performance levels and long-term reliability.

LOGISTIC INFORMATION

Packaging



Basic plastic bag

- Height (cm) : 1
- Length (cm) : 40
- Depth (cm) : 15
- Net weight (kg) : 0.26
- Gross weight (kg) : 0.27



Outer package 1



Carton box

- Height (cm) : 46
- Length (cm) : 36
- Depth (cm) : 27
- Net weight (kg) : 21.3
- Gross weight (kg) : 22.3



Outer package 2



Pallet

- Height (cm) : 118
- Length (cm) : 120
- Depth (cm) : 80
- Net weight (kg) : 446
- Gross weight (kg) : 466



x 1600.00