

# Steel wire rope Ø 2.5 mm x 150 m



## Characteristics

Cable Ø (mm) : **2.5**  
Length (m) : **150**

## GENERAL INFORMATION

### Technical details

Braided steel cable.  
Strand core: 7 x 7 steel wires.

### Advice

For use with locking devices BIZ 710 405, BIZ 710 406, and BIZ 710 408 in upright position only.

### Application(s)

Create wire loops for static light-duty suspensions.

## ADDITIONAL INFORMATION

Locking devices for integrated locking system compatible with Ø 1.5 and 2.5 mm steel cables.

Maximum load (Ø 1.5 mm cable): 35 kg\*. Maximum load (Ø 2.5 mm cable): 70 kg\*. \* The resistances given for the BIZ 710 365 and BIZ 710 366 locking devices are designed to be used with cables BIZ 710 360, BIZ 710 361, BIZ 710 363 and BIZ 710 364.

APAVE test report available on request.

Arrows indicating the cable entry and exit directions make it possible to create suspension loops simply, rapidly, and securely. Unlocks simply by pressing. Rapid adjustment and modification of length is possible after the object to be suspended has been installed.

## LOGISTIC INFORMATION

### Packaging



#### Reel

Height (cm) : 10  
Length (cm) : 14  
Depth (cm) : 14  
Net weight (kg) : 3.7  
Gross weight (kg) : 3.8



### Outer package 1



#### Carton box

Height (cm) : 11  
Length (cm) : 29  
Depth (cm) : 29  
Net weight (kg) : 14.8  
Gross weight (kg) : 15.2

x 4



### Outer package 2



#### Pallet

Height (cm) : 80  
Length (cm) : 90  
Depth (cm) : 90  
Net weight (kg) : 799  
Gross weight (kg) : 820



x 216