ISO & PG step drill bit Ø 10 mm 12 steps

Ideal for electricians!





Caracteristics

Drilling Ø (mm): 6.5-32.5 Shank Ø (mm): 10 Hardness (HRC): 65-66 Numbers of floors: 12

Materials

⊘ Metal

Benefits

- Fast chip evacuation by helix flute increases cutting capacity.
- 5 % cobalt steel for constant drilling temperature and for long life.
- Drilling accuracy with offset point.

GENERAL INFORMATION

Description

Compatible with PG and ISO. 12 laser marked steps.

Three flats milled on Ø 10 mm shank to prevent slipping in the chuck.

Technical details

Hexagonal shank 10 mm Ø. 5 % cobalt HSS steel. Helix flutes. Cross shaped sharpening.

Advice

Use cutting oil to extend the tool's lifetime.

Application(s)

Drills through metal sheet up to 2 mm thick. For drilling non-ferrous metals, stainless steel and synthetic materials up to 4 mm thickness.

LOGISTIC INFORMATION

Packaging



Plastic case

Height (cm): 5 Length (cm): 11.5 Depth (cm): 5 Net weight (kg): 0.20 Gross weight (kg): 0.25 3"700420"300885

Outer package 1



Carton box

Height (cm): 38.8 Length (cm): 28.8 Depth (cm): 19

Net weight (kg): 10
Gross weight (kg): 10.4

