

5000ETP10W

C-Bus - Ethernet touch panel - 10" - white cover frame



Main

Range	C-Bus
Product or component type	Touch panel
Device application	Equipment monitoring and control
Display colour	262000 colours
Display size	10.1 inch
Provided equipment	1 screw 1 mounting plate 1 cover frame 10 fixing screws 4 washer 1 desk stand 1 micro SD card securing plate 1 Ethernet cable securing plate
Cover frame colour tint	White

Complementary

Supply	External power supply- 12 V DC (+/- 5 %) - 1.5 A Via PoE- 15 W
Power consumption in W	6 W (typical)
Standby consumption	< 0.5 W
Display resolution	1280 x 800 pixels
Luminance	300 cd/m ²
View angle horiz x vert	170° horizontal 170° vertical
Communication port protocol	Ethernet
Port Ethernet	10/100BASE
Integrated connection type	Audio output USB port HDMI Ethernet port Micro SD card port
Connector type	Power input
Contrast ratio	800:1
Aspect ratio	16:9
Response time	30 ms (typical)
Mounting location	Wall mounting
Device mounting	Flush Surface
Width	Cover frame : 316 mm
Height	Cover frame : 220 mm
Depth	Cover frame : 6 mm

Environment

ambient air temperature for operation	0...40 °C
relative humidity	10...85 %
standards	IEEE 802.3af

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.