

## 755LPSMA4

FireTek - smoke alarm - photoelectric - surface mounted - lithium battery powered



### Main

Range	Firetek
Product brand	Clipsal
Product or component type	Smoke detector
Device application	Early detection of smouldering fires and open fires
Electronic sensor type	Photo-electric sensor

### Complementary

Power supply type	Battery
Battery type	Lithium
Battery life	10 yr
[Ie] rated operational current	70 mA
Control type	Button for test/hush function
Number of devices	40 for wireless alarm
Operating distance	50 m indoor use line of sight 50 m indoor use line of sight 140 m in free field
Response time	< 30 s
Transmission frequency	433420 kHz
Noise level	85 dB at 3 m minimum
Time delay range	10 min for hush 10 h for do not disturb
Local signalling	Sound : alarm Sound : signal Visual : 1 LED (red) for low battery indication Visual : 1 LED (red, green and blue) for wireless function status
Type of installation	Indoor
Mounting support	Wall Ceiling
Diameter	130 mm
Depth	37.5 mm

### Environment

ambient air temperature for operation	0...45 °C
relative humidity	5...95 %
product certifications	RCM Activfire SAI
standards	ISO 8201 AS 3786: 2014

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1818 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.