ALC: NO.	-	Concernances of the local division of the lo	and the second se	
10000	and the second		State of State	
10000	Ward Internation	the designed of the second	- Name of Street, or other	
press of	the second s	an partition and the	and the second second	
page 1	Contractory of the local division of the loc	the feature containing	Contraction of the local division of the loc	
98000		an descentioners		
\$60.000	And in case of the second	a protection and		
1000		-		
		and provide and the	and the second second	
		-		
₽F			-	
	RE	-	-	
	RE	7		
	UDED 🕁			-

Includes flywire mesh sheet to eliminate entry of insects.



EPFL/PFL EXTERNAL FIXED LOUVRE GRILLE



- Designed to withstand harsh outdoor conditions, made with impact & UV resistant Polypropylene.
- Includes flywire mesh sheet to eliminate entry of insects.
- Available in 100mm, 125mm, 150mm & 200mm.

MODEL NO. (SINGLE UNIT ONLY)	MODEL NO. (FOR BULK PACK)	NO. OF GRILLES IN BULK PACK	DUCT DIAMETER AØ	B□	с	D
EPFL100	EPFL100	20	100	155	16	29
EPFL125	EPFL125	10	125	155	16	29
EPFL150	EPFL150	10	150	186	17	37
PFL200PK	PFL200	15	200	248 All	25 dimensio	30 ons in mm



DIMENSIONS



PGL EXTERNAL GRAVITY LOUVRE GRILLE



- Designed to withstand harsh outdoor conditions, made with impact & UV resistant PVC.
- Includes shutters that open when the fan is running and close when it is off.
- Available in 100mm, 125mm & 150mm.

MODEL NO. (SINGLE UNIT ONLY)	MODEL NO. (FOR BULK PACK)	NO. OF GRILLES IN BULK PACK	DUCT DIAMETER AØ	B□	с	D	E
PGL100PK	PGL100	20	100	155	15	25	18
PGL125PK	PGL125	10	125	155	17	28	20
PGL150PK	PGL150	10	150	185	15	35	20
					All	dimensio	ns in mm



ALUMINIUM EXTERNAL FIXED LOUVRE GRILLE



- Comes with a galvanised steel spigot that fits inside the wall cavity, leaving the front face to finish flush to the wall.
- Its rigidly-fixed horizontal blades are designed to reduce the possibility of rainwater entry.
- Vermin proof mesh is fitted to minimise the entry of debris.

MODEL NO.	DUCT DIAMETER AØ	в□	с	D	E	F
ELDA200	200	297	60	95	20	250
ELDA250	250	345	60	95	25	300
				A	All dimens	ions in mn



DIMENSIONS



EXTERNAL EAVE GRILLE





The Under Eave Vent EEVSS is made from high quality 316 grade stainless steel, and has been designed for general air intake or exhaust applications. It is fitted with a sturdy wire mesh that prevents pests from entering.

- Flush mounting ideal for under-eave venting.
- Can be used for air intake or exhaust.
- Wire mesh face allows it to be used for wall or ceiling mounting also.
- Made from high quality 316 marine grade Stainless Steel.
- Cinder Mesh insert for compliance with Bushfire Attack Level BAL -40.
- Mounting gasket forms an air-tight seal.

MODEL NO.	А	в	с	D	E	F
EEVSS100	143	130	86	96	4	50
EEVSS150	206	189	135	145	4	58
					All d	limensions in mm

DOME VENT EXTERNAL GRILLE

304 GRADE

STAINLESS

STEEL



The stainless steel Dome Vent is designed for external wall mounting. It is suitable for areas with harsh weather and the mesh screen prevents pests and insects from entering.

- Ideal for extreme weather conditions.
- High quality 304 stainless steel.

MADE

CV6H

- Includes mounting gasket for an air tight seal.
- Cinder mesh with a 2mm aperture to comply with Bushfire Attack Level BAL-40.

	MODEL NO.	DUCT DIAMETER AØ	в	с	D
_	EDVSS100	100	130	147	50
D	EDVSS125	125	165	187	50
-	EDVSS150	150	189	210	60
				All din	nensions in mm



DIMENSIONS



DØ



DIMENSIONS



© FANTECH TRADE 2023

HOOD VENT EXTERNAL GRILLE





All dimensions in mm

The Hood Vent is made from high quality 304 stainless steel and has a gravity backdraft shutter that prevents cold air flowing back into the room. The valve body is equipped with a mounting gasket that forms an air tight seal.

- Ideal for extreme weather conditions.
- Includes gravity backdraft shutter.
- Cinder mesh with a 2mm aperture to comply with Bushfire Attack Level BAL-40.

MODEL NO.	DUCT DIAMETER AØ	В	с	D	E
EHVSS100	100	156	50	58	156
EHVSS125	125	180	50	66	184
EHVSS150	150	181	58	78	184