

# NSYPLAZ12104G

Floor standing encl.polyester vers.PLAZ w/plinth  
open bottom 1250x1000x420 IP54



## Main

|                           |  |
|---------------------------|--|
| Range                     | Thalassa   |
| Product name              | Thalassa PLA   |
| Device application        | Multi-purpose  |
| Product or component type | Suitable enclosure   |
| Device short name         | PLAZ   |
| Enclosure nominal height  | 1250 mm  |
| Enclosure nominal width   | 1000 mm  |
| Enclosure nominal depth   | 420 mm   |
| Enclosure mounting        | Floor-standing   |
| Device composition        | 2 rear panel<br>2 door<br>1 plinth<br>2 side part<br>1 top part<br>1 bottom part |

## Complementary

|                             |   |
|-----------------------------|---|
| Body type                   | Sealed top and open bottom part assembled with side parts |
| Door type                   | Plain front   |
| Number of doors             | 2   |
| Door opening side           | Right and left 120 °                                      |
| Lock type                   | 4 points lock, handle with 5 mm double bar insert         |
| Accessibility for operation | Front<br>Rear<br>Bottom                                   |
| Removable parts             | Door by hinges<br>Rear panel by fixing element            |
| Material                    | Polyester reinforced with fibreglass                      |
| Colour                      | Grey RAL 7035   |
| Standards                   | IEC 62208   |
| Product certifications      | Veritas   |

## Environment

|                                     |  |
|-------------------------------------|--|
| IP degree of protection             | IP54 plinth type open bottom IEC 60529 |
| IK degree of protection             | IK10 plain door IEC 62262              |
| fire resistance                     | 960 °C IEC 62208                       |
| ambient air temperature for storage | -35...90 °C                            |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 1511 - Schneider Electric declaration of conformity |
| REACH                            | Reference not containing SVHC above the threshold                     |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations                                 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.