



Main

Range	Linergy
Product name	BW
Product or component type	Busbar support
Device short name	LA9Z
Quantity per set	Set of 10

Complementary

Range compatibility	TeSys
Poles description	4P
Permissible current	200 A with 12 x 5 mm busbar 250 A with 15 x 5 mm busbar 320 A with 20 x 5 mm busbar 400 A with 25 x 5 mm busbar 450 A with 30 x 5 mm busbar 360 A with 12 x 10 mm busbar 520 A with 20 x 10 mm busbar 630 A with 30 x 10 mm busbar
[Ui] rated insulation voltage	690 V conforming to IEC 60947-1 690 V conforming to NF C 20-040
Distance between supports	570 mm
Busbar pitch	60 mm
Colour	Grey

Environment

IP degree of protection	IP20 with protective cover
temperature resistance	125 °C
standards	UL 508 IEC 61439-2
product certifications	IEC

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0626 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.