

NSYDLP198G

DLP modular dist chassis 198modules(18mm)
insulating material for PLA H1000xW750



Main

Range	Thalassa
Accessory / separate part category	Mounting accessory
Device application	Multi-purpose Modular distribution application
Product or component type	Chassis
Device short name	DLP
Enclosure nominal dimensions	
Mounting location	Front of enclosure
Range compatibility	Thalassa PLA
Device composition	1 chassis structure 1 neutral/earth strip 2 x 16 mm ² 5 x 6 mm ² 6 front panels with 35 mm DIN rail
Additional information	IP2x not respected when chassis is mounted at 67 mm

Complementary

Material	Self-extinguishing for front panel Galvanised steel for chassis structure and rails
Colour	Front panel : grey RAL 7035
Fixing mode	By fixing element - on front with supports location
Adjustment	In height from 40 to 85 mm for DIN rail
Number of horizontal rows	6
Total number of 18 mm modules	198
Type of front plate	Cut-out plate
Number of cut-out	6 cut-outs
Height	1000 mm
Width	750 mm

Environment

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1511 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.