

EVP1CBS323C45

Attached cable T2 32A 3-Ph IEC 4,5m Smart Wallbox



Main

Range	EVlink
Product or component type	Charging cable
Accessory / separate part category	Spare part
Network number of phases	Three phase
Poles description	3P + N
[In] rated current	32 A
[Us] rated supply voltage	380...415 V AC 50/60 Hz
Earthing system	Compatible TT Compatible TN Compatible IT with additional isolation transformer on the power supply
Nominal output power	22 W 32 A
Socket number	1

Complementary

Connector type	Without connector charging station end T2 vehicle end silver plated contacts
Range compatibility	EVlink Smart Wallbox EVB1 charging station
Standards	IEC 62196-1 IEC 62196-2
Product certifications	CE
Length	4.5 m
Product weight	3.5 kg

Environment

IP degree of protection	IP54 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
ambient air temperature for operation	-30...50 °C
ambient air temperature for storage	-40...80 °C
relative humidity	5...95 %

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.