



### Main

Range of product	Altivar
Product or component type	Communication module

### Complementary

Range compatibility	Lexium 32 Altivar Process Modular Altivar Machine ATV340 except Sercos drives Altivar Machine ATV320 Altivar Process ATV900 Altivar 32
Product compatibility	Lexium 32
Communication port protocol	EtherCAT
Electrical connection	2 connectors RJ45
Transmission rate	100 Mbps
Cable distance between devices	<= 100 m for 100 Mbps
Addressing	Position addressing Node addressing Logical addressing
Communication service	PDO and SDO support Drive profile CiA 402 velocity mode conforming to IEC 61800-7-201 (CiA 402) CANopen over EtherCAT (CoE)
Display type	1 LED input status 1 LED RUN 1 LED error 1 LED output status

### Environment

standards	IEC 61800-7-201 (CiA 402)
-----------	---------------------------

### Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.