

## NSYZZ553G

Polyester glassrein. plinth for encl. PLAZ(T)53 front opening IP44-IK10 RAL7035



### Main

Range	Thalassa
Accessory / separate part category	Enclosure accessory
Product or component type	Plinth
Device application	Multi-purpose
Enclosure nominal dimensions	
Device composition	2 front panel Fixing elements 2 side part
Range compatibility	Thalassa PLA

### Complementary

Fixing mode	By screws - on side parts location
Colour	Plinth : grey RAL 7035
Height	500 mm
Width	535 mm
Depth	310 mm

### Environment

IP degree of protection	IP44
IK degree of protection	IK10

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1511 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.