

NSYPAP75G

reversible internal door polyester 2 locks grid pattern
for PLM75



Main

Range	Thalassa
Accessory / separate part category	Enclosure accessory
Product or component type	Door
Device application	Multi-purpose
Enclosure nominal dimensions	
Mounting location	Front side
Range compatibility	Thalassa PLM
Device composition	1 door 1 handle 4 fixing brackets

Complementary

Material	Polyester charged with fibreglass
Colour	Grey RAL 7035
Lock type	Lock 5 mm double bar
Number of locks	2
Door type	Internal plain
Door opening side	Reversible 110 °
Height	Grid pattern : 615 mm
Width	Grid pattern : 405 mm
Depth	Available depth between enclosure door : 32 mm Available depth between rear : 244 mm

Environment

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1511 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.