



Main

Range of product	500 Series
Product or component type	Switch
Quantity per set	Set of 10
Type of packing	Carton
Colour tint	White
Motor M-rating AS3133	M50

Complementary

Control type	Rocker
Material	PC (polycarbonate)
Installation direction	Vertical
Surface finish	Gloss
Width	66 mm
Height	66 mm
Diameter	66 mm
Rated current	16 A/16 AX
[Ue] rated operational voltage	250 V AC 50 Hz
Network number of phases	1 phase
Number of gangs	1 gang
Number of poles	1
Connections - terminals	3 screw terminal
Clamping connection capacity	4 x 1.5 mm ² 2 x 1.5 mm ²
Device mounting	Ceiling
Fixing center	50 mm

Environment

Ambient air temperature for operation	-10...40 °C
---------------------------------------	-------------

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	Download RoHS China Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.