


SAU25024273

Acti 9 Chassis - iC60 250A, 3Ph, 27mm, 24pole, Top Feed



Main

| | |
|---------------------------|--------------|
| Range | Acti 9 |
| Product or component type | Chassis |
| Device application | Distribution |

Complementary

| | |
|-------------------------|---------------------------|
| Range compatibility | Acti 9 distribution board |
| Network type | AC |
| [In] rated current | 250 A |
| Short-circuit withstand | 25 kA for 0.1 s |
| Number of ways | 1-incomer-3P |
| Number of poles | 24 27 mm |
| Location of connection | Top |
| Length | 326 mm |
| Width | 215 mm |
| Busbar pitch | 27 mm |

Environment

Offer Sustainability

| | |
|--------------------------|---------------------------|
| Sustainable offer status | Not Green Premium product |
|--------------------------|---------------------------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.