NSYPLM43G

wall-mounting enclosure polyester monobloc IP66 H430xW330xD200mm





Main

Dongo	Thalassa
Range	Halassa
Product name	Thalassa PLM
Device short name	PLM
Device application	Multi-purpose
Product or component type	Compact enclosure
Enclosure nominal height	430 mm
Enclosure nominal width	330 mm
Enclosure nominal depth	200 mm
Enclosure mounting	Wall mounted
Device composition	Lock 2 Door 1 Body 1
Body type	One piece moulded with notches in the rear Built-in canopy
Door type	Plain
Lock type	3 mm double-bar lock

Complementary

Number of locks	2	
Mounting plate description	Without mounting plate	
Accessibility for operation	Front	
Removable parts	Door by hinges	_
Material	Polyester reinforced with fibreglass	
Colour	Grey RAL 7035	_
Standards	IEC 62208 NEMA classification 13 NEMA classification 4X	
Product certifications	UL	

Environment

		-
IP degree of protection	IP66 IEC 60529	- Sinda
IK degree of protection	IK10 IEC 62262	
fire resistance	960 °C IEC 62208	
ambient air temperature for storage	-3590 °C	

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1511 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations