

# NSYPLAZ554G

Floor standing encl.polyester vers.PLAZ w/plinth  
open bottom 500x500x420 IP54



## Main

Range	Thalassa
Product name	Thalassa PLA
Device application	Multi-purpose
Product or component type	Suitable enclosure
Device short name	PLAZ
Enclosure nominal height	500 mm
Enclosure nominal width	500 mm
Enclosure nominal depth	420 mm
Enclosure mounting	Floor-standing
Device composition	1 door 1 rear panel 1 plinth 2 side part 1 top part 1 bottom part

## Complementary

Body type	Sealed top and open bottom part assembled with side parts
Door type	Plain front
Number of doors	1
Door opening side	Reversible 120 °
Lock type	2 points handle lock, 5 mm double-bar
Accessibility for operation	Front Rear Bottom
Removable parts	Door by hinges Rear panel by fixing element
Material	Polyester reinforced with fibreglass
Colour	Grey RAL 7035
Standards	IEC 62208
Product certifications	Veritas

## Environment

IP degree of protection	IP54 plinth type open bottom IEC 60529
IK degree of protection	IK10 plain door IEC 62262
fire resistance	960 °C IEC 62208
ambient air temperature for storage	-35...90 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1511 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.