Product datasheet
Characteristics

NSYDLP297G
DLP modular dist chassis 297modules(18mm) insulating material for PLA H1500xW750

Main

Range	Thalassa
Accessory / separate part category	Mounting accessory
Device application	Multi-purpose Modular distribution application
Product or component type	Chassis
Device short name	DLP
Enclosure nominal dimensions	
Mounting location	Front of enclosure
Range compatibility	Thalassa PLA
Device composition	1 chassis structure 1 neutral/earth strip 2 x 16 mm² 5 x 6 mm² 9 front panels with 35 mm DIN rail
Additional information	IP2x not respected when chassis is mounted at 67 mm

Complementary

Material	Self-extinguishing for front panel Galvanised steel for chassis structure and rails
Colour	Front panel : grey RAL 7035
Fixing mode	By fixing element - on front with supports location
Adjustment	In height from 40 to 85 mm for DIN rail
Number of horizontal rows	9
Total number of 18 mm modules	297
Type of front plate	Cut-out plate
Number of cut-out	9 cut-outs
Height	1500 mm
Width	750 mm

Environment

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1511 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations