



Main

Range of product	PDL General Accessories
Product or component type	Socket
Colour tint	White
Quantity per set	Set of 25 Set of 800
Type of packing	Carton

Complementary

Material	Plastic PC (polycarbonate)
Surface finish	Glossy
[In] rated current	10 A
[Ue] rated operational voltage	230/240 V AC 50 Hz 240 V AC 50 Hz
Network number of phases	1 phase
Number of gangs	1 gang
Socket number	3
Installation direction	Vertical
Mounting support	Panel
Height	32 mm
Width	38 mm
Diameter	2.3 mm
Fixing center	38 x 32 mm
Connections - terminals	6.35 mm ² spade terminal

Environment

ambient air temperature for operation	-10...40 °C
---------------------------------------	-------------

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1809 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.