

3025RCD30-VW

Clipsal Iconic - 2 switched sockets - RCD 30 mA - vivid white



Main

Range	Clipsal Iconic
Product or component type	Switched socket
Device presentation	Complete product
Outlet poles configuration	2P + E with shutter
Type of packing	Polybag
Quantity per set	Set of 4
Sale per indivisible quantity	1
Rated current	10 A, 250 V AC, 50 Hz

Complementary

Number of power socket outlets	2
Device mounting	Flush
Number of rocker	2
Outlet standard	Australian
Outlet standard description	With earthing contact
Outlet standard	Australian/New Zealand
Ground lug position	Straight 180° position
Fixing mode	By screw
Installation direction	Horizontal
Colour tint	Vivid white (VW)
Surface finish	Matt
Ambient air temperature for storage	0...60 °C
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Electrical durability	12000 cycles
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	1 x 2.5...4 x 2.5 mm ² (rigid) 1 x 2.5...4 x 2.5 mm ² (rigid) 1 x 2.5...4 x 2.5 mm ² (stranded) 1 x 2.5...4 x 2.5 mm ² (flexible)
Wire stripping length	16 mm
Material	ABS (acrylonitrile butadiene-styrene) for cover frame POM (polyoxymethylene) for shutter POM (polyoxymethylene) for shutter PC (polycarbonate) for fixing frame PP (polypropylene) for rocker PC (polycarbonate) for cover frame
Height	120 mm
Width	78 mm
Depth	44 mm
Standards	AS/NZS 3112 AS/NZS 3190

Environment