


# TRIPROOF

TRIPROOF20W06-TRI

SAP CODE: 2001164




600mm, 20W, Tritone, rugged indoor/outdoor batten

A robust and powerful outdoor/indoor IK08 vandal resistant LED batten with Tritone switchable colour temperature.

Accessories  
SUSPENSION KIT



Photometric Diagram



Unit: cd  
- C0/180 110.0deg  
- C90/270 110.0deg

## KEY INFORMATION

Lumen Output 20W	1850 / 1990 / 1850lm
Input Power	20W
Hole Cutout Size	N/A
Dimming Options	Non-Dimmable
Trim Colour	WHITE
Warranty	5yr
IP Rating	IP65
IK Rating	IK08
IC Rating	N/A
Rebate Scheme Approvals	N/A

## PHOTOMETRIC

Efficacy 20W	93 / 100 / 93lm/W
LED	SMD
CCT	4000 / 5000 / 6500K
CRI	>80
Beam Angle	120°

## ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	20-57VDC
Power Factor	>0.9
LED Input Current (nominal)	350mA
Useful life @Ta25° (L70)	50,000hr

## CONSTRUCTION

Housing	Polycarbonate
Optic	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	Terminal Block PA14
Total Weight	2kg
Dimensions	618x116x74mm
Operating Ambient Temp.	-30 to 50°C
Electrical Classification	Class 1
Food Grade Approval	HACCP