

3000K WARM WHITE | **4000K** COOL WHITE | **5000K** NATURAL WHITE



240V	8W	3000K 4000K 5000K		 100° BEAM ANGLE	CRI(Ra) >83	POWER FACTOR 0.80	 90mm	 IP44	
------	----	-------------------------	--	------------------------	----------------	-------------------------	----------	----------	--

FEATURES

- Switchable between Warm White (3000K), Cool White (4000K) & Natural White (5000K).
- Can be abutted against or covered with thermal building insulation.
- Fixed head downlight.
- Moulded plastic body.
- Recessed diffused front lens
- Wide 100 degree beam angle.
- High efficiency SMD LED Array.
- Integrated dimmable LED driver.
- Long lasting up to 30,000 hours¹.
- 0.6m flex & plug plus terminals for hardwiring.
- IP44 (front only).
- 5 Year Warranty.

MAIN APPLICATIONS

All interior residential rooms.

APPROVALS

VEET (ESC): 7102

MODEL NO.	WATTAGE (W)	LUMENS @ 3000K (lm)	LUMENS @ 4000K (lm)	LUMENS @ 5000K (lm)	COLOUR
20429/05	8	780	900	880	WHITE

¹ Actual life may vary depending on individual circumstances.

