




12V AC/DC 3U LED GLOBES



Product Features:

- Input voltage: 12V AC/DC 50/60Hz
- Nominal current: 1A
- Material: PBT & glass
- Wattage: 9W
- LED chips: 48pcs 2835 LED
- Ambient Temp: -15 to 50°C (The life of the lamp will gradually reduce if used outside these temperature parameters)
- Not suitable for dimming
- Recommended iron core(only) transformer & Constant Voltage LED driver



Part No.	Description	Lamp holder	Kelvin (K)	Lumens (LM)	Watt (W)	Length (mm)	Diam (mm)	Weight (kg)	Box (cm)	Carton QTY
3U001	GLOBE LED 12V AC/DC ES 3U	E27	3000	720	9	140	Ø41	0.1	16x4.5x4.5	1/100
3U002	GLOBE LED 12V AC/DC ES 3U	E27	4000	760	9	140	Ø41	0.1	16x4.5x4.5	1/100
3U003	GLOBE LED 12V AC/DC ES 3U	E27	6500	780	9	140	Ø41	0.1	16x4.5x4.5	1/100

Recommended Transformer or Driver:

S.N.	Brand	Part No.	Type	QTY of Lamps
1	CLA	CLA113011	LED Driver	1-2 pcs
2	CLA	CLA115011	LED Driver	1-4 pcs
3	CLA	CLA1110011	LED Driver	1-7 pcs
4	CLA	CLA1115011	LED Driver	1-12 pcs
5	CLA	CLA1120011	LED Driver	2-17 pcs
6	AQUATRAN	AQ012-050/1415	Iron Core Transformer	1-4 pcs

When calculating quantity of lamps to be used per driver or transformer:

Minimum Load: 10% of rated power;

Maximum Load: 80% of rated power.