



Main

Range of product	Preventa Safety automation
Accessory / separate part type	Connecting cable
Accessory / separate part category	Cabling accessory
Accessory / separate part destination	Safe speed monitoring module Drive MC4

Complementary

Product compatibility	XPSMCMEN0... PacDrive M
Cable length	3 m
Electrical connection	Connector : female SUB-D 9 shielded, elbowed for PacDrive M motor Connector : male SUB-D 9 shielded, elbowed for PacDrive M drive Connector : RJ45, straight for XPSMCMEN0...
AWG gauge	AWG 24
Communication network category	5e
Type of cable	Twisted unshielded pairs cable cable : red
Product weight	0.31 kg

Environment

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1510 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.