

VZ1L007UM50

line choke - 5 mH - 7 A - 1 phase - 20 W - for
variable speed drive



Main

Range of product	Altivar
Product or component type	Line choke
Product compatibility	ATV312H055M2 - line choke - 1 per drive ATV312H075M2 - line choke - 1 per drive ATV31C055M2 - line choke - 1 per drive ATV31C075M2 - line choke - 1 per drive ATV32H055M2 - line choke - 1 per drive ATV32H075M2 - line choke - 1 per drive LXM05D10F1 - line choke - 1 per drive LXM05D10M2 - line choke - 1 per drive LXM32.U45M2 - line choke - 1 per drive Variable speed drive ATV320 motor : 0.55 kW 200...240 V - single phase - line choke - 1 per drive Variable speed drive ATV320 motor : 0.75 kW 200...240 V - single phase - line choke - 1 per drive
Network number of phases	Single phase
Range compatibility	Altivar 312 Lexium 05 Altivar 32 Lexium 32 Altivar 31C Altivar 312 Solar Altivar Machine ATV320
Device application	Reduction of current harmonics
Value of inductance	5 mH
[In] rated current	7 A
Thermal losses	20 W

Complementary

Supply frequency	50...60 Hz
Voltage drop at rated load	5 %
Product weight	0.88 kg
Width	60 mm
Height	100 mm
Depth	95 mm


Environment

standards	EN 50178 IEC 60076 (with HD398) VDE 0160 level 1
IP degree of protection	IP00 (choke) IP20 (terminals)

Single-Phase Line Choke

Dimensions

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



Dimensions in mm

a	b	c	G	H	Ø (oblong hole)
60	100	95	50	60	4 x 9

Dimensions in in.

a	b	c	G	H	Ø (oblong hole)
2.36	3.94	3.74	1.97	2.36	0.16 x 0.35