

AS2293.3 APPENDIX B

DECLARATION OF COMPLIANCE FOR EMERGENCY ESCAPE LUMINAIRES AND EXIT SIGNS

(INFORMATIVE)

Manufacturer: Evolt Pty Ltd
Address: U5/105a Vanessa Street,
 Kingsgrove, NSW 2208, Australia



Last updated: 4 November 2020_V1.0

EMERGENCY ESCAPE LUMINAIRE / EXIT SIGN			
ORDER CODE	PRODUCT NUMBER	SKU	QTY
EV-BOXIT-CEILING-24M Basic Ceiling Mounted Emergency Exit	9336462150023	15002	4
<input type="checkbox"/> Emergency escape luminaire	<input type="checkbox"/> Centrally supplied		
<input checked="" type="checkbox"/> Exit sign	<input checked="" type="checkbox"/> Self-contained		
<input checked="" type="checkbox"/> Maintained	<input type="checkbox"/> Non-maintained		
<input checked="" type="checkbox"/> Combined			

WALTEK (CNAS L9950)	
TEST	DESCRIPTION
Safety Standards	IEC 60598-1:2014+A1:2017 IEC 60598-2-22:2014 IEC 60598-2-1:1979/AMD1:1987 EN 60598-1:2015+A1:2018 / EN 60598-2-22:2014 EN 60598-2-1:1989 / EN 62493:2015 AS/NZS 60598.2.22:2005 AS/NZS 60598.2.1:2014+A1:2016 AS/NZS 60598.1:2017+Amdt
Safety Certification	NO105266
Safety / Performance Test Report	352994
EMC standards	EN 55015:2013/A1:2015 EN 6100-3-2:2014 EN 61000-3-3:2013 EN 61547:2009 AS/NZS CISPR 15: 2011
EMC Certification	352994
EMC Test Report	352994

LIGHTLAB	
AS2293 TESTING	DESCRIPTION
Thermal Report	LL1827906T
Photometric Report	LL21516
Pictogram Report	LL21515 / LL21515
Classification	E2 E2.5

OPERATIONAL INFORMATION	
GENERAL	
Mains Voltage	240V~ 50Hz
Ambient temp.	0 to 40°C
Class	2
Diffuser type	Polycarbonate
BATTERY	
Number of cells	1
Type	LiFePO ₄
Nominal Voltage	3.2 V
Capacity	1500mAh
Part number	1300

DECLARATION OF COMPLIANCE

On the basis of the test reports specified, I declare that the emergency escape luminaire/ exit sign described in this document complies with the requirements of AS2293.3.

Title: Managing Director **Date:** 27/10/20

Signature:

NOTE: This declaration form should be completed in full. The completed form should be considered sufficient to verify compliance with AS 2293.3.

ektor.com.au
E: sales@evolt.com.au
P: 1300 4EVOLT (438 658)

evolt
 the electrical evolution

Ektor is dedicated to continuous product improvement. Datasheet is subject to change without notice, E&OE. Images are for illustrative purposes only.