



Platinum Exit LED Weather Proof Nexus LX Picto

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.



Representative Photo Only  
(actual product may vary based on configuration selections)

**SPECIFICATIONS**

Component Type	Emergency Lighting	Exit
Testing System		Nexus LX
Operating Mode		Maintained
Operating Voltage		240 VAC
Rated Frequency		50 Hz
Power Consumption		3.2 W
Mounting		Surface - Wall
Viewing Distance		24 meters
LED Life		100,000 hours
Photometric Classification		C0:D1.25 C90:C1.25
Battery Type		LiFePO4
Height		190 mm
Width		130 mm
Depth		380 mm
Base Colour		Grey
Diffuser Colour		White on Green
Battery Replacement		0301301P
IP Rating		IP65
Standards Compliance		ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005

# Catalogue No: **PWEXNXSLEDP1**

## PLATINUM EXIT LED WEATHER PROOF NEXUS LX PICTO

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Exit LX



### REFERENCES

IECEX Certificate

-

Supplier Declaration of Conformity:

[Weatherproof LED Exit Sign, NiCad or LifePO4 Battery\\_Supplier Declaration of Conformity \(SDoC\)](#)

Installation Guide:

[Stanilite Exit LED Weatherproof Standard, Nexus LX, Nexus RF\\_Installation Instructions](#)

User Manual:

-

Manufacturer Datasheet:

[Platinum Exit LED Weatherproof Nexus\\_Manufacturer Datasheet](#)

Manufacturer Catalogue & Product Selection:

-