

RJ6U24PPC

Clipsal Patch Panel Flat 19" 1U 24-port Keystone UTP Loaded Cat6 Non-shutter



Main

| | |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product | Actassi |
| Product brand | Clipsal |
| Product or component type | Patch panel |
| Device application | Punch down tool Quick termination tool |
| Device presentation | Loaded |
| Provided equipment | Side cover 2 6 U/UTP inside the enclosure Label holder 3 inside the rack Removable cable tray 1 Ports identification at the rear 24 With RJ45 connectors 24 |
| Colour | Grey (RAL 7040) |
| Colour code | TIA-568A/B |
| Quantity per set | Set of 1 |

Complementary

| | |
|--------------------------------|------------------------------------|
| [In] rated current | 1.5 A at 25 °C |
| Dielectric strength | 1000 V |
| Connections - terminals | IDC |
| Connector type | 24 RJ45 Cat. 6 U/UTP |
| AWG gauge | AWG 24...AWG 23 |
| Cable outer diameter | 0.9...1.4 mm |
| Cable shielding type | U/UTP |
| Communication network category | 6 |
| Communication port support | Ethernet |
| Contact resistance | 20 mOhm |
| Insulation resistance | >= 500 MOhm |
| Mounting support | 19" rack |
| Minimum number of matings | 750 cycles |
| Number of rack unit | 1U |
| Number of pairs | 4 pairs |
| Installation direction | 90° |
| Type of connector | S-110 keystone |
| Material | ABS + PC + metal TIA-568A/B 1.5 mm |
| Width | 482 mm |
| Depth | 124 mm |
| Height | 44 mm |
| Net weight | 1 kg |
| | Asia Pacific |

Environment

| | |
|---------------------------------------|-----------------------------------------------------------------------------------------------|
| Ambient air temperature for operation | -10...60 °C |
| Ambient air temperature for storage | -20...70 °C |
| Relative humidity | 0...93 % |
| Standards | ISO/IEC 11801:2011 Ed.2.2 ANSI/TIA-568-C.2 IEC 60603-7-2 AS/NZS 3080:2003 UL 1863 |
| Product certifications | UL listed conforming to UL 94 V0 RCM conforming to RoHS compliant |

Offer Sustainability

| | |
|-------------------|---------------------|
| EU RoHS Directive | Under investigation |
|-------------------|---------------------|