

Catalogue No: **561132**

HC TERMINAL 290A IN/OUT 1xM10(LUG 10-120mm BUSBAR 20-24mm)

Power Distribution and Protection > Busbar, Chassis and Power Connections > Power Connections > High Current Terminals (Power Terminals/Blocks) > High Current Terminals > Power Terminal (Bolt to Bolt) - SBLL



High Current Terminal 290A Cu input/output 1xM10 (lug 10-120mm busbar 20-24mm)

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

| | |
|------------------------------------------------|-------------------------------------------------|
| Component Type Power Distribution & Protection | High Current Terminal |
| In, Rated Current | 290 A |
| Icw, short time withstand current, 1s (rms) | 14.4 kA for 1s |
| Ipk, Peak Current, Max | 42000 A |
| Ui, Rated Insulation Voltage, AC | 1000 V AC |
| Ui, Rated Insulation Voltage, DC | 1500 V DC |
| Flammability Rating (UL94) | UL 94 V-1 |
| Halogen Free | Yes |
| Quantity, In | 1 |
| Wire / Conductor Size, Flex Cable, In, Min | 10 mm ² In |
| Wire / Conductor Size, Flex Cable, In, Max | 120 mm ² In |
| Wire / Conductor Size, Rigid Cable, In, Min | 10 mm ² In |
| Wire / Conductor Size, Rigid Cable, In, Max | 120 mm ² In |
| Screw Size, In | M10 (120 mm ²) In |
| Quantity, Out | 1 |
| Screw Size, Out | M10 (120 mm ²) Out |
| IP Rating | IP20 |
| Height | 205.7 mm |
| Width | 52.3 mm |
| Depth | 65 mm |
| Weight | 0.16 kg |
| Standards Compliance | CE, ERIFLEX SB CSA 70044370 cURus RoHS |
| Certifications | C-UL-US |

Catalogue No: **561132**

HC TERMINAL 290A IN/OUT 1xM10(LUG 10-120mm BUSBAR 20-24mm)

Power Distribution and Protection > Busbar, Chassis and Power Connections > Power Connections > High Current
Terminals (Power Terminals/Blocks) > High Current Terminals > Power Terminal (Bolt to Bolt) - SBLL



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -