

ULTRA SLIM MULTI OUTPUT LED DOWNLIGHTS

The MR10 and MR13 Multi XC both feature M-Elec's revolutionary new eXchangable Connector system allowing multiple AC connection options for fast and reliable installation. retrofit installations. Coming complete with extra wide trim With an all new driver design and multi output colour selection technology, the MR10/MR13 Multi XC combines warm white, neutral white and white outputs all in one eliminating the need to juggle different fittings.

The ultra slim profile (only 33mm deep) to suit minimum ceiling clearance makes this light perfect for both new and (white) to make retrofits easy and the XC compatible flex and plug, M-Elec's MR10/MR13 Multi XC is designed with the electrical contractor in mind!





Designed for electricians!
These downlights feature great efficacy at competitive prices.

Technical information

	ML-MR10-MULTI-XC	ML-MR13-MULTI-XC
Total power consumed:	10W*	13W*
Lumen output:	760lm (WW) 880lm (NW) 790lm (W)	1,130lm (WW) 1,260lm (NW) 1,190lm (W)
Colour temperature:	3,000K (WW) 4,000K (NW) 6,000K (W)	
IP rating:	IP54	
CRI:	80+	
Efficacy:	80-84 lm/W	94-97lm/w
Beam angle:	100 degrees	
Dimmable:	Yes	
Power supply:	200-240V AC External driver 50-60 Hz (ML-MR10MDXC)	200-240V AC External driver 50-60 Hz (ML-MR13MDXC)
Average life:	50,000hrs**	
Diameter:	122 mm Depth 33 mm Cut-out 90 mm	
Optional upgrades:	Silver trim (ML-MR90-TS) Surface mount enclosure (ML-MRSMT-90) RAPID XC Connector (ML-BSRC-XC)	
Compliance:	AS/NZS 60598.1 & AS/NZS 60598.2.2	
Connection:	With XC connector flex and AU plug	

^{*}Total power consumed including driver



^{***} Life span is calculated on expected average lifespan