



## 24M 2Row DIN Flush Metal BOX, No Door

VT24F

### Functions

|             |         |
|-------------|---------|
| Ventilation | without |
|-------------|---------|

### Compatibility

|                                      |        |
|--------------------------------------|--------|
| Cabinet profile measurement standard | metric |
| Suitable for lightning protection    | yes    |

### Main electrical features

|                 |                |
|-----------------|----------------|
| Nominal voltage | 230 / 415 V AC |
|-----------------|----------------|

### Cover, door

|                              |                |
|------------------------------|----------------|
| Material thickness cover     | 1 mm           |
| Interlockable                | no             |
| Cover type                   | Closed (plain) |
| Door lock can be sealed      | no             |
| Door leave                   | without        |
| Symmetric doors (same width) | no             |
| Cover type                   | Cover          |
| Door included                | no             |
| Transparent cover or door    | no             |

### Materials

|                           |                       |
|---------------------------|-----------------------|
| Colour                    | light grey            |
| RAL colour                | RAL 9002 - Grey white |
| Material                  | Steel                 |
| Material quality          | Steel                 |
| Surface appearance        | satın finish          |
| Type of surface treatment | Painted               |

### Dimensions

|                             |        |
|-----------------------------|--------|
| Insertion depth             | 60 mm  |
| Depth of wall niche         | 70 mm  |
| Depth of installed product  | 10 mm  |
| Internal depth              | 68 mm  |
| Height of installed product | 464 mm |
| Width of installed product  | 414 mm |
| Width in division units     | 12     |

Technical Properties

|                                |        |
|--------------------------------|--------|
| Thickness of sidewall material | 1 mm   |
| Built-in width                 | 364 mm |

**Installation, mounting**

|                              |     |
|------------------------------|-----|
| Suitable for outdoor use     | no  |
| Suitable for ground mounting | no  |
| Suitable for wall mounting   | yes |

**Accessories included**

|                         |    |
|-------------------------|----|
| Mounting plate included | no |
|-------------------------|----|

**Equipment**

|                    |    |
|--------------------|----|
| Number of rows     | 2  |
| Quantity of rails  | 2  |
| On/Off switch      | no |
| Extension possible | no |

**Standards**

|           |                |
|-----------|----------------|
| Approvals | AS/NZS 61439-3 |
|-----------|----------------|

**Safety**

|   |                             |
|---|-----------------------------|
| IK protection code against mechanical impacts | IK05                        |
| Protection class                              | isol.class I                |
| Glow wire test                                | according to AS/NZS 61439-1 |
| Halogen free                                  | no                          |
| Fire resistance                               | -                           |