

# Starburst Crystal ECO LED GEN II Downlight

## CRYSECO5G2

- One box solution with 2-in-1 cut-out sizes and fixed or gimble formats
- Cut-out 90mm, adjustable to 70mm by removing posts on trim
- Install as a fixed downlight by using the locking ring in the box



### Performance

|                           |                     |
|---------------------------|---------------------|
| System Power              | 9W                  |
| Exit Lumen                | 880lm               |
| Efficacy                  | 77lm/W              |
| CCT                       | 4000K               |
| CRI                       | 80                  |
| Operating Temperature     | 0°C to 40°C         |
| MacAdam Steps             | 3SDCM               |
| Ingress Protection Rating | IP20                |
| Beam Distribution         | Symmetric           |
| Beam Angle                | 60°                 |
| Warranty                  | 3 Years             |
| Lifetime                  | 30,000hrs (L70/B50) |


### Physical

|                    |                      |
|--------------------|----------------------|
| Dimensions         | Ø110 x H81mm         |
| Cutout Diameter    | 90mm                 |
| Reflector          | Aluminium            |
| Luminaire Colour   | White                |
| Weight             | 0.70kg               |
| Luminaire Material | Aluminium (Die Cast) |
| Driver Location    | Integrated           |
| Heatsink           | Aluminium (Die Cast) |
| Finish             | Powder Coated        |
| Installation       | Recessed             |

### Electrical

|                         |         |
|-------------------------|---------|
| Dimming                 | Phase   |
| Voltage                 | 240V    |
| Inrush Current          | 4A      |
| Inrush Current Duration | 310µs   |
| Line Current            | 0.04A   |
| Electrical Rating       | Class 2 |

### Line Drawings



### Product Images



