

Cable gland nylon black ISO/M5.2 Ø 30-38 mm IP 68 (x 2)



Characteristics

Mounting Hole (mm) : **50.2**
 Minimum cable Ø (mm) : **30**
 Maximum cable Ø (mm) : **38**
 Inside Ø (mm) : **38.5**
 Quantity : **2**
 Selling unit : **Each**

Norms

> IP 68

Compliance marks



GENERAL INFORMATION

Description

Contents: locknut, washer, body, seal and nut.

Technical details

Material: UL approved polyamide 6.6.
 Flammability: UL 94V-2.
 Operating temperature: -20 °C + 100 °C
 Metric Pitch: 1.5 mm.
 Colour: black.
 Halogen free.

Application(s)

Can be mounted directly onto pre-drilled panel hole using the locknut or can be directly screwed onto metric threaded holes.

LOGISTIC INFORMATION

Packaging



No packaging

Height (cm) : 7.4
 Length (cm) : 7.2
 Depth (cm) : 7.2
 Net weight (kg) : 0.11
 Gross weight (kg) : 0.11



Outer package 1



x 2

Carton box

Height (cm) : 12
 Length (cm) : 17
 Depth (cm) : 9
 Net weight (kg) : 0.21
 Gross weight (kg) : 0.21



Outer package 2



x 60

Carton box

Height (cm) : 31.5
 Length (cm) : 61
 Depth (cm) : 37
 Net weight (kg) : 6.81
 Gross weight (kg) : 7.88

