

Cable gland nylon black ISO/M40.2 Ø 22-32 mm IP68 (x 5)



Characteristics

Mounting Hole (mm) : **40.2**
 Minimum cable Ø (mm) : **22**
 Maximum cable Ø (mm) : **32**
 Inside Ø (mm) : **32.5**
 Quantity : **5**
 Selling unit : **Each**

Norms

> IP 68

Compliance marks



GENERAL INFORMATION

Description

Contents: locknut, washer, body, seal and nut.

Technical details

Material: UL approved polyamide 6.6.
 Flammability: UL 94V-2.
 Operating temperature: -20 °C + 100 °C
 Metric Pitch: 1.5 mm.
 Colour: black.
 Halogen free.

Application(s)

Can be mounted directly onto pre-drilled panel hole using the locknut or can be directly screwed onto metric threaded holes.

LOGISTIC INFORMATION

Packaging



No packaging

Height (cm) : 6
 Length (cm) : 7.4
 Depth (cm) : 7.4
 Net weight (kg) : 0.09
 Gross weight (kg) : 0.09



Outer package 1



x 5

Carton box

Height (cm) : 12
 Length (cm) : 17
 Depth (cm) : 9
 Net weight (kg) : 0.44
 Gross weight (kg) : 0.44



Outer package 2



x 150

Carton box

Height (cm) : 31.5
 Length (cm) : 61
 Depth (cm) : 37
 Net weight (kg) : 12.16
 Gross weight (kg) : 13.23

