

FULTON INDUSTRIES AUSTRALIA PTY. LIMITED ABN: 53 003 971 417 PO BOX 6258, WEST GOSFORD NSW 2250







ACCREDITED ISO9001, ISO14001, & AS4801

DATA SHEET GOOD EARTH

EARTHING COMPOUND



	BENTONITE AND
DESCRIPTION	GYPSUM EARTHING
	COMPOUND
SIZE (mm)	550H x 300W x 140D
COLOUR	WHITE BAG
WEIGHT (kg)	15 kg

MATERIAL: Bentonite and Gypsum

HARDWARE: N/A

TESTING: SAFETY DATA SHEET AVAILABLE UPON REQUEST

SALES DRAWING No: N/A

NOTE: Bentonite and Gypsum mixture to be used in Earthing Installation

A 15kg Bag covers approximately 0.03 m³

Mixing: Add clean water gradually to mixture and mix slowly until a pourable slurry is achieved.

Normal Mixture: Soil, Clay, Shale, Sandstone, Ironstone –

1 litre Water to 0.5kg GOOD EARTH

Medium Mixture: Saturated (Clay, Shale, Sandstone) Sand –

1 litre Water to 0.8kg GOOD EARTH

Gravel or holes with excessive seepage or filled with water – **Strong Mixture:**

1 litre Water to 1kg GOOD EARTH

Use mixture within twenty minutes of mixing

Create Date: 01/05/2019

Version 1 Revision Date: - Created: S Taylor Checked: D Podger Approved: M Donnelly