

Cable tie Stainless steel 200 x 4.6 mm (x 100)



Characteristics

Length (mm) : **200**
 Width (mm) : **4.6**
 Maximum clamping Ø (mm) : **51**
 Traction strength (N) : **540**
 Quantity per bag : **100**

Benefits

- May be tightened by hand.
- Ball locking system.

GENERAL INFORMATION

Technical details

Class 304 stainless steel.
 Salt-spray resistance: no red rust after 48 hrs.
 Thickness: 0.26 mm.
 Temperature resistance: -80 to +538 °C.
 Halogen-free.

Advice

For easier fitting, use pliers BIZ790010.

Application(s)

Recommended for use in corrosive environments (food, chemical and dairy industry, hospitals, etc.).

LOGISTIC INFORMATION

Packaging



Basic plastic bag

Height (cm) : 1
 Length (cm) : 28
 Depth (cm) : 11
 Net weight (kg) : 0.26
 Gross weight (kg) : 0.27



Outer package 1



Carton box

Height (cm) : 22
 Length (cm) : 30
 Depth (cm) : 23
 Net weight (kg) : 13
 Gross weight (kg) : 14



x 50.00

Outer package 2



Pallet

Height (cm) : 120
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 835
 Gross weight (kg) : 904



x 3250.00