

## PREMIUM Exit and Emergency Luminaires

### EZYLEDLP - All-in-one Exit

All-in-one exit complete with all variations of running man decals. Features Sentinel Automatic Self-testing and LiFePO<sub>4</sub> battery technology with Battery Management System to maximise battery life.



#### Features and Benefits

- In-built Sentinel Automatic testing capability
- High output LEDs for bright consistent & efficient light distribution
- Lithium Iron Phosphate battery including integrated battery management system (BMS) to maximise battery life
- Complete with all variations of the "Running Man" decal pack with a 24m viewing distance
- Wall or Ceiling Mountable
- Over 2 hours runtime in emergency mode.
- Designed and manufactured in accordance to AS/NZS 2293



EZYLEDLP		
<b>Input</b>	<b>Operating Voltage</b>	230V
	<b>Frequency</b>	50Hz
<b>Output</b>	<b>LED Array</b>	12 x Everlight 67-21S LEDs
	<b>Light Source</b>	3W
	<b>Function</b>	Maintained
	<b>Power Consumption (LEDs)</b>	4W
<b>Battery</b>	<b>Type</b>	LiFePO <sub>4</sub>
	<b>Charger</b>	Variable current CV
	<b>Protection</b>	Charger overcharge and low voltage disconnect
	<b>Autonomy Duration</b>	Minimum 2 hours
<b>Physical</b>	<b>IP Classification</b>	IP20
	<b>Weight</b>	1.4kg
	<b>Dimensions (LxWxH)</b>	375x65x225mm
	<b>Construction</b>	Fire Retardant ABS V0
<b>Installation</b>	<b>Mounting</b>	Surface. Wall or Ceiling.
<b>Environment</b>	<b>Temperature</b>	0°C - 40°C
	<b>Relative Humidity</b>	0 - 95%
<b>Conformance</b>	<b>C0</b>	D3.2
	<b>C90</b>	E2.5
	<b>Standards</b>	AS/NZS 2293, EMC
<b>Warranty</b>	<b>Duration</b>	Fitting: 5 Years / Battery: 1 Year
<b>Intelligence</b>	<b>Sentinel</b>	In-built
	<b>WiNetRF</b>	Compatible

\*Guaranteed to meet runtime requirements of AS/NZ 2293 throughout warranty duration.

ACCESSORY	DESCRIPTION
<b>BEL-901890</b>	Wall mount wire guard for EZYLEDLP
<b>BEL-901891</b>	Ceiling mount wire guard for EZYLEDLP
<b>BEL-31511</b>	Replacement battery for EZYLEDLP

SPACING TABLE	MOUNTING HEIGHT (m)			
NATA Classification	2.1	2.4	2.7	3.0
C0 - D3.2 (m)	6.5	6.5	6.5	6.5
C90 - E2.5 (m)	5.4	5.6	5.8	5.8

\*Refer to AS/NZ 2293 for complete spacing table.