



Platinum Batten IP65 600mm Maintained RF 2500 lumens



- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

Representative Photo Only  
(actual product may vary based on configuration selections)

**SPECIFICATIONS**

Component Type	Emergency Lighting	Batten
Testing System		Nexus RF Infinity
Operating Mode		Maintained
Operating Voltage		240 VAC
Rated Frequency		50 Hz
Power Consumption		25.0 W
Mounting		Surface - Universal
LED Life		75,000 hours
Lumen Output		2500 lumens
Photometric Classification		C0:D40 C90:D63
Battery Type		LiFePO4
Height		90 mm
Width		140 mm
Depth		660 mm
Base Colour		Grey
Diffuser Colour		Frosted
Battery Replacement		0301307P
IP Rating		IP65
IK Rating		IK08
Standards Compliance		ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005

Catalogue No: **PBLWRF25LM**

PLATINUM BATTEN IP65 600mm MAINTAINED RF 2500lm

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Batten RF



## REFERENCES

IECEX Certificate

-

Supplier Declaration of  
Conformity:

[Weatherproof LED Battens, NiCad or LifePO4 Battery\\_Supplier Declaration of Conformity \(SDoC\)](#)

Installation Guide:

[Stanilite Batten LED Weatherproof Standard, Nexus® LX, Nexus RF\\_Installation Instructions](#)

User Manual:

-

Manufacturer Datasheet:

[Platinum Batten LED Weatherproof Nexus - 2 Foot\\_Manufacturer Datasheet](#)

Manufacturer Catalogue  
& Product Selection:

-