



Platinum Spitfire Dual LED Weather Proof Surface Mount Nexus RF



- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

Representative Photo Only  
(actual product may vary based on configuration selections)

**SPECIFICATIONS**

Component Type	Emergency Lighting	Spitfire
Testing System		Nexus RF Infinity
Operating Mode		Non-Maintained
Operating Voltage		240 VAC
Rated Frequency		50 Hz
Power Consumption		1.0 W
Mounting		Surface - Ceiling
LED Life		100,000 hours
Photometric Classification		C0:D63 C90:D63
Battery Type		LiFePO4
Height		130 mm
Width		188 mm
Depth		278 mm
Base Colour		Grey
Battery Replacement		0301303P
IP Rating		IP67
Standards Compliance		ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005

Catalogue No: **SFBWPNRF2LEDP**

**PLATINUM SPITFIRE DUAL LED W/PROOF SURFACE MOUNT NEXUS RF**

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Spitfire RF



#### REFERENCES

IECEX Certificate -

Supplier Declaration of  
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: [Platinum Spitfire LED Weatherproof Nexus Non-maintained\\_\\_Manufacturer Datasheet](#)

Manufacturer Catalogue  
& Product Selection: -