

# Stanilite®

## Platinum exit LED Quickfit® Nexus®



### Range

Platinum range

### Product group

Exit LED Quickfit



### Features



- LED technology 100,000 hours plus lamp life
- Low power consumption and LED light source for reduced operation and maintenance costs
- Advanced charging technology combined with Lithium iron phosphate battery for long life and low maintenance
- Nexus monitored, either cabled or wireless
- Quickfit unique steel slide connect bracket for quick installation and easy maintenance
- Includes all pictograph diffuser options for single or double sided installation
- Universal wall/ceiling mounting, can also be rod or wire suspended
- Retrofit capability; fits into any existing Quickfit mounting bracket
- Frame only available for upgrade of installed product (less mounting bracket and diffusers) - will accept existing diffusers

Catalogue no.	Description
<b>Nexus products</b>	
PQFNXSLEDP	Platinum exit LED Quickfit Nexus LX pictograph
PQFNRFLEDP	Platinum exit LED Quickfit Nexus RF pictograph
<b>Accessories</b>	
MQFCL	Cantilever bracket
QFWGCM	Wire guard - ceiling
QFWGWM	Wire guard - wall
PWQFKITPOLY	IP65 kit - polycarbonate for single or double sided installation
PWQFKITACRY	IP65 kit - acrylic for single or double sided installation
29-PIQFVERT	Quickfit pictograph vertical insert pack 4 piece set *
Note: * Refer to the installation manual for vertical installation requirements	
<b>Spare parts</b>	
03-01302P	Battery LiFePO4 3.2V 3.2Ah
31-PQF	Diffuser Quickfit LED includes single sided pictograph decal
PQFNXSLEDP-LB	Platinum exit LED Quickfit less bracket Nexus LX pictograph
PQFNRFLEDP-LB	Platinum exit LED Quickfit less bracket Nexus RF pictograph
PQFNXSLEDP-FR	Platinum exit LED Quickfit frame only Nexus LX
PQFNRFLEDP-FR	Platinum exit LED Quickfit frame only Nexus RF



Dimensions			
	Length	Width	Height (incl. bracket)
	379mm	72mm	214mm
Weight			
Model	Weight		
Nexus LX/RF	1.8kg		

<b>Construction</b>		
<b>Part</b>	<b>Construction</b>	
Body	UV/FR ABS body	
Diffuser	Opal acrylic	
Bracket	White powder coated zinc steel	
<b>Light source</b>		
<b>Model</b>	<b>Light source</b>	
Nexus LX/RF	Multiple LED 1.6W	
<b>Power consumption</b>		
<b>Model</b>	<b>Power consumption</b>	
Nexus LX/RF	3.2W	
Note: Preliminary results		
<b>Photometrics</b>		
<b>Model</b>	<b>Class</b>	<b>Classification</b>
Nexus LX/RF	C0	D3.2
	C90	D3.2
Note: Preliminary results		

Note:

- Designed to comply with AS2293 and meet relevant Australian EMC standards