

## CLEVERTRONICS ECONOMY LITHIUM ODYSSEY QUANTUM LED DIFFUSED BATTEN



### PRODUCT INFORMATION

Part Number	EBS2LEDS-DIF-LI
MIC	AUB03510020001
Description	Economy Lithium 2ft Odyssey Quantum LEDdiffused batten
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface mount
Dimensions L x W x H	630mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Acrylic Prismatic
Driver / Ballast	Osram 40W, 500-1050mA, 15-50V
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	2250 lm @ 118lm/W
Power Consumption	19 Watts (Lamps ON), 0.4 Watts (Lamps OFF)
IP Rating	IP20
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D50 C <sub>90</sub> =C50

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560156	BATT:LiFePO4 3.2V 3.0Ah 200mm lead, BRKT
8002695	PCA:LED Strip 8S6P, ALS-13-840-0-02-B
1330029	LED Driver - 40W, 500-1050mA, 15-50V
ELIFE-X-LI-CKIT-2LED-SL-NP	Lifelight, Control Only,2LED,3.0Ah,325mA