

ODYSSEY QUANTUM DIFFUSED

ODYSSEY QUANTUM DIFFUSED 1200MM

| ORDERING INFORMATION | | EL | | LP | | 240V | |
|--------------------------|-----------------------|------------------------|--------------------|------------------------|----------------------|------------------------|-------------------|
| Nominal Size | | 1200mm | | 1200mm | | 1200mm | |
| TEST OPTIONS PART NO. | Standard | EBS4LEDS-DIF-LI | EBS4LEDS-LO-DIF-LI | CBS4LEDS-DIF | CBS4LEDS-LO-DIF | FBS4LED-DIF | FBS4LED-LO-DIF |
| | DALI Driver | - | - | CBS4LEDS-DIF-DD | CBS4LEDS-LO-DIF-DD | FBS4LED-DIF-DD | FBS4LED-LO-DIF-DD |
| | Motion Sensors ■ | Yes (High/Low) | | | | | |
| | CTP System Compatible | No | | Yes | | - | |
| | DALI | - | | CBS4LEDS-DIF-DALI | CBS4LEDS-LO-DIF-DALI | - | |
| | Zoneworks® XT Hive | - | | CBS4LEDS-DIF-HV | CBS4LEDS-LO-DIF-HV | - | |
| Carton Quantity | | 1 | | | | | |
| Weight - single (carton) | | 3.3kg | 3.3kg | 3.3kg | 3.3kg | 3.0kg | 3.0kg |
| Dimensions (L x W x H) | | 1238mm x 120mm x 108mm | | 1271mm x 120mm x 108mm | | 1238mm x 120mm x 108mm | |

■ For Motion sensor version add -MS-HL to the product code as per the following example. EBS4LEDS-DIF-MS-HL-LI

| TECHNICAL SPECIFICATIONS | | EL | | LP | | 240V | |
|--|--|--|------------|------------|------------|--------|--------|
| Construction - Base | | Powder Coated steel | | | | | |
| Construction - Diffuser | | Acrylic Prismatic | | | | | |
| Voltage (V) (Frequency (Hz)) | | 220-240V (50Hz) | | | | | |
| Power Consumption ♦ (Standby / Max) | | 0.4W / 39W | 0.4W / 19W | 0.4W / 39W | 0.4W / 19W | 39W | 19W |
| Lamp(s) (CCT / Life) ♦ | | 4000K / 50,000hrs (L70 / B50 Ra>80 Ta40) | | | | | |
| Lamp | | LED Strip Module | | | | | |
| Nominal Total Light Output ♦ | | 4500lm | 2250lm | 4500lm | 2250lm | 4500lm | 2250lm |
| Operating Temperature | | 1°C to 40°C | | | | | |
| Ingress Protection Rating (IP) | | IP20 | | | | | |

♦ Please refer to the specific product data sheet for actual power, light output, lamp lifetime and driver values.

| EMERGENCY SPECIFICATIONS | | EL | | LP | |
|--------------------------|--|--|--|----------------|--|
| Operating Mode | | Sustained | | | |
| Battery Configuration | | Integral | | POD | |
| Battery Type | | Lithium Iron Phosphate | | | |
| Voltage / Capacity (mAh) | | 3.2V / 3000mAh | | 3.2V / 3200mAh | |
| Charging Method | | Intelligent Current Limited Constant Voltage | | | |

| CLASSIFICATION | | EL | | LP | |
|----------------|--|-----|--|-----|--|
| Co | | D50 | | D40 | |
| C90 | | D16 | | D40 | |

| SPARE PARTS | | EL | | LP | | 240V | |
|-------------|--|---------|--|---------|--|---------|--|
| Battery | | 1560156 | | 1550050 | | - | |
| LED Strip | | 8002695 | | 8002695 | | 8002695 | |