ULTRABLADE PRO SURFACE MOUNT EXIT

ORDERING INFORMATION	EL ECONOMY	CLP PREMIUM	L10	
Standard - White	EUBPRO-SM-LI	CUBPRO-SM	LUBPRO-SM	
Standard - Black	-	CUBPRO-SM-BLK	LUBPRO-SM-BLK	
Clevertest Plus System compatible	No	Yes	Yes	
DALI®	-	CUBPRO-SM-DALI	LUBPRO-SM-DALI	
Zoneworks® XT	-	CUBPRO-SM-ZW	LUBPRO-SM-ZW	
Carton Quantity		5		
Weight – single (carton)		1.1kg / 7.5kg		
Dimensions (L x W x H)		"317mm x 8.7mm x 157mm - Blade Assembly 360mm x 47mm x 72mm - Base"		
Directional Options	All direction	All directional inserts included in the box (Up, Down, Left, Right)		
Directional Options (Theatre Only)	-	Add Suffix to Part Number, -DS Double Sided, -R Pictograph, L (Left) or R (Right) ie. CUBPRO-SM-TH-DS-RR		


^{*} for additional variants please refer to the Clevertronics Product Guide or website.

POWER, LAMPS AND BATTERY	EL ECONOMY	CLP PREMIUM	L10
Power Consumption (Standby / Max)	1.5W / 2.5W	1.8W / 3.9W	1.9W / 4.1W
Lamp(s)	50,000hrs LEDs	100,000hrs LEDs	
Battery	Lithium Iron Phosphate		Lithium Nanophosphate®
Voltage (V) / Milliamp per hour (mAh)	3.2V / 1500mAh	3.2V / 3200mAh	3.3V / 2500mAh
Charging Method	Intelligent current limited constant voltage		
Rated Emergency Duration (Mins)	180		

TECHNICAL SPECIFICATIONS				
Operating Mode	Maintained			
Voltage (V) Frequency (Hz)	220-240V(50Hz)			
Construction - Body	ABS / PC			
Viewing Distance	30m			
Mounting type	Wall & Ceiling (single & double sided)			
Operating Temperature	1°C to 40°C			
IP Rating (IP)	IP20			

SPARE PARTS	EL	CLP	L10
Battery	1560100	1550030	1530030
Lamp Bar	8002179	8002178	8002178
DALI® Node	-	8003061	8003061
Zoneworks® Node	-	8001450	8001450
Diffuser	2310250	2310250	2310250

PROTECTION	
Battery overvoltage & overcurrent protection	
Battery deep discharge protection	
Supply voltage polarity reversal protection	
Battery short-circuit protection (charging will resume upon removal of fault)	



Dimensions (mm)

^{*}Warranty information located at: https://clevertronics.co.uk/product-warranty-statement/
The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.