



CLEVERTRONICS LP 600mm (2ft) NON-MAINTAINED WEATHERPROOF BATTEN REPLACEMENT



Gen 1



Gen 2

Fittings are supplied without tubes

PRODUCT INFORMATION

Catalogue Number	CWB2N-P
Description	LP Premium Weatherproof Batten Emergency with LED Emergency POD, Enabled with Clevertest Plus
Construction	Polycarbonate Base and Diffuser with Powdercoated Metal Gear Tray and Tamper proof Stainless Steel Clips
Mounting	Surface Mount
Dimensions L x W x H	720mm x 160mm x 105mm
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Lamp(s)	2 x 3W LED
Operating Voltage	240V AC; 50Hz
Power Consumption	1.0 Watts (Standby), 3.9 Watts (Max)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40
Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
2750370	LP WP Batten Lifelight POD & Battery
CLIFE-PRO-CKIT-NP	LifelightPro, Control Only, Batten, LP, NP

