

CLEVERTRONICS L10 OPTIMUM LIFELIGHT PRO CYLINDER SURFACE MOUNT EMERGENCY



PRODUCT INFORMATION

Catalogue Number	LLIFE-PRO-SMC
Description	L10 Lifelight PRO, High Performance, Cylinder Surface Mount Emergency Light with Lithium Battery Technology, Enabled with Clevertest Plus
Mounting	Surface Mount
Dimensions L x W x H	128mm (D), 252mm (L)
Ceiling hole cut-out	N/A
Minimum ceiling depth	N/A
Operating Mode	Non-Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Ballast	N/A
Charging Method	Intelligent current limited constant voltage charger
Lamps(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V 50Hz
Power Consumption	0.4W (Standby), 2.2W (max during 16 hour charge)
IP Rating	IP20
Impact Rating	N/A
Operating Temperature	1° to 40°C (Ambient)
AS/NZ2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1100830	Lamps: 2 x 3W LED Round Head Assembly - White
1530230	Battery: 3.3V 5Ah.Li-ion, 200mm lead with Bracket
LLIFE-PRO-SMC-CKIT-NP	PCA: Lifelight Pro Control Gear

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order