

## CLEVERTRONICS LP LIFELIGHT PRO RECESSED IP65 WEATHERPROOF EMERGENCY



### PRODUCT INFORMATION

Part Number	CLIFE-PRO-RECWP-WHT
MIC	AUT02320060001
Description	LP Premium LifeLight PRO, high performance, IP65 recessed Emergency Light with remote gear, Enabled with Clevertest Plus
Construction	Die Cast Aluminium Body 316 Stainless Steel Screws Clear Toughened Glass
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 120mm head diameter
Ceiling Hole Cut-Out	106mm
Minimum Ceiling Depth	120mm
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)
IP Rating	IP65 (Lamp head only)
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D40 C <sub>90</sub> =D40
Impact Rating	IK10

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
CLIFE-PRO-CKIT	Lifelight Pro, Control Only, LP Lithium
1100843	Lifelight Pro Head Assembly, Round, Blk, Gen 2

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order*